



Accessory

The SafeHome Wireless Alarm system can be divided into 8 zones – each with an unlimited amount of sensors, sirens and dial-up units.

Customize your alarm to fit your needs!

Wireless Autodialer (PSTN)

Accessory for Wireless Alarm System WS500S

SafeHome Wireless Alarmsystem WS500S can be expanded with an automatic dialer, which when alarm is triggered dials up to 8 receivers and plays a pre-recorded message. The Wireless Autodialer WS100-V2 can be used with standard analogue phonenumber (PSTN).

The autodialer is wirelessly connected to the controlpanel and thereby offers the best possible security as it will continue the dialup cycle - even if the controlpanel is sabotaged.

Receivers of the alarmcall can by use of the autodialer's speaker address - or by use of the microphone listen to - the surroundings.

HOTLINE SUPPORT • YOUTUBE • FACEBOOK



SafeHome Trådløse Alarmanlæg kan udbygges med opkaldsenhed, så der ved alarm automatisk ringes op til maks. 8 numre, og afgiver en indtalt besked. Den automatiske opkaldsenhed WS110-V2 kan benyttes med alm. fastnet telefonlinje (PSTN).

Den trådløse automatiske opkaldsenhed tilkobles trådløst til alarmanlægget og sikrer dermed bedst muligt ved indbrud, da den vil fortsætte sin opkaldscyklus selvom kontrolpanelet ødelægges.

Modtagerne af opkaldet kan enten via opkaldsenhedens højttaler tale til,- eller via opkaldsenhedens mikrofon lytte til,- omgivelserne.



Logistical data	PN	Dimension (HxBxW)cm	Weight (kg)	Quantity	EAN
Unit (blister)	278016-NORDIC	22,5x15,3x10	0,417	-	5704842003803
Inner carton	-	25,8x23x16,5	1,8	4	5704842003841
Export carton	-	47,5x27x35,5	7,3	16	5704842003889
EU pallet (180cm)	-	180x80x120*	-	320	-

*) 4 layers, 5 exp. carton/layer

Features / KSP

- Autodials to 8 receivers
- Place in safe distance to entrance
- Connects to analogue line (PSTN)
- Up to 100m range
- Easy Installation
- Powerplug and backupbattery
- Alarmsign Included

Tech specs

- Connection: Cabled to PSTN line
- Dimensions (mm)/weight (g): 54/15/15, 169
- Battery: 4 x 1,5V AA Alkaline (not incl.)
- Power: (in/out): 100-240V (50/60Hz)/9,5V, 0,5A.
- Power cons: 4,75W
- With screws, plugs, adhesive tape
- Frequency: 868 MHz

Packing specs

- Blister pack, Eurohanger
- 4 language (UK, DK/SE/NO)

Accessory for Wireless Alarm System WS-500S